



FLOORTOP

eco

Ecological high-performance maintenance cleaner

Area of application

FLOORTOP ECO is suitable for cleaning and maintaining all water-resistant floor coverings, such as linoleum, PVC, caoutchouc / rubber, olefin, PUR annealed floor covers, sealed wood / parquet floor / cork, laminate and natural stone tiles. For coated and uncoated water-resistant floor coverings. To be used with ALL cleaning procedures. Suitable for anti-static floor coverings when applied properly.



Application

Manual maintenance cleaning of normal contamination: 0.25%

Mechanical cleaning: 0.5 – 1.0%

Spray cleaning: 1.3%

Apply the cleaning solution using fresh, cold water.

Interim cleaning/maintenance:

- Maintenance or initial treatment: Dilute 1:10 with fresh water (10%), wipe clean surface and polish once dry (high-speed machine to high-speed polishing machine).
- Spray cleaners: Dilute 1:3 – 1:5 with fresh water, partially apply using a spray pump and treat the surface using a high-speed machine (400 – 450 U/min).
- Interim cleaning: Dilute 1:10 with fresh water (10%), apply solution, mechanically treat (e.g. single-disc machine), remove residue and polish once dry (high-speed machine to high-speed polishing machine).

The correct dosage reduces costs and helps the environment.



Product characteristics

- Certified with the European Union Ecolabel (EU Ecolabel) and the Cradle to Cradle Gold Certificate
- Cleaning, maintenance and revitalisation in one work step
- Strong wetting properties and high dirt-dissolving properties
- Suitable for antistatic floors when used properly
- Tested according to DIN 18032 (sports halls - halls and areas for sport and multipurpose use).
- Streak-free shine - can be polished to achieve excellent shine
- Non-slip, non-textured maintenance film
- Pleasant room fragrance

Note

To minimise plastic use and reduce carbon emissions, we recommend refilling the 1-litre container from the 10-litre canister using a drain valve. Do not wet mop sealed wooden / parquet floors, cork and laminate floor coverings! Only damp-wipe with little remaining moisture.



Service

FLOORTOP ECO helps to reduce CO₂ emissions. We make your savings potential transparent and also offer carbon neutralisation with the help of a CO₂ calculator.

Speak to your advisor or contact us directly on +49 893506080 or ksc@dr-schnell.com

pH conc

0	2	4	6	10	12	14
---	---	---	---	----	----	----

Technical information

Carton of 12 x 1 l bottles
10 l canister

Order No. 00994
Order No. 30999



All information contained in our brochures is accurate to the best of our knowledge and experience. No liability can be derived from the information herein. For details about the product, please refer to the safety data sheet. (GB) 1121

DR.SCHNELL GmbH & Co. KGaA
Taunusstraße 19 · 80807 Munich
Tel. +49 89 3506080
info@dr-schnell.com
www.dr-schnell.com

Wir leben Hygiene
DR.SCHNELL
QUALITÄT UND SERVICE